


# PRODUCT DATASHEET

Electrical testing accordance with:  
 《GB/T5968-2011》  
 《GB/T5966-2011》  
 LCA standard test

Do not Scale this Drawing  
 Unit : mm



|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                |                    |               |        |                  |                 |                |                |                                          |                                                                                       |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|--------------------|---------------|--------|------------------|-----------------|----------------|----------------|------------------------------------------|---------------------------------------------------------------------------------------|--|
| Capacitance                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Cap. Tolerance | Dissipation Factor | Rated Voltage | D.W.V. | Rated Current(A) | I.R.(100VDC)    | Temp. Coef.    | Temp. Range    |                                          |                                                                                       |  |
| 1000pF                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | -20%+80%       | ≤3.5%              | 100VDC        | 300VDC | 10               | ≥3000MΩ         | X7R            | -55℃+125℃      |                                          |                                                                                       |  |
| Min. No Load Insertion Loss (dB)@25℃                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                |                    |               |        |                  |                 | Install Torque | Soldering Temp | CIRCUIT                                  |                                                                                       |  |
| 10KHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 100KHz         | 1MHz               | 10MHz         | 100MHz | 1GHz             | 10GHz           |                |                |                                          |                                                                                       |  |
| --                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | --             | --                 | 5             | 15     | 30               | 40              | 0.3 N·m        | ≤300℃/3S       | C                                        |  |  |
| <p>Material and other parameter note:</p> <p>1. The case material is silver-plated brass, and the lead material is silver-plated brass.</p> <p>2. Encapsulated with epoxy resin.</p> <p>3. The above data is measured under 25℃ conditions, and the electrical performance test frequency is 1KHz/1V.</p> <p>4. It is recommended to use a soldering iron for soldering. Immersion soldering is strictly prohibited, and the capacitor body must not be struck with hard objects.</p> |                |                    |               |        |                  | Revision Record | 200508-01      |                | Product Series                           | Thread Mount Feedthrough Filters                                                      |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                |                    |               |        |                  |                 | 260128-01      |                | <div>LCA®</div> <div>made in China</div> | <div>L6040-093</div>                                                                  |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                |                    |               |        |                  |                 |                |                |                                          |                                                                                       |  |